



LITE RAILING 60

Code: EWD60X42

Delivers a lighter visual profile with clean contemporary lines for modern balconies, terraces and outdoor spaces.

Suitable For: Railing hand rails, railing verticals, louvers, screens, ducting coverings, facade features, interior and exterior baffle walls & ceilings.



AVAILABLE COLOURS



OAK



MAHOGANY

TECHNICAL SPECIFICATIONS

Series	Name	Surface	Length(mm)	Width(mm)	Thickness(mm)	Wt/No (Kg)	Area/Pc(Sq.ft)	PCS/Pack
Louver & Rail	Lite Rail 60	Brushed	2900	60	42	5.95	1.87	4

*Digital representation of the product & colour is limited and will vary from the actual product in colour and texture.

COMPARE WPC RAILINGS & LOUVERS

IMAGE					
SERIES	LITE - RAILING 75	LITE - RAILING 70	LITE - RAILING 60	LITE - LOUVER 50	LITE - LOUVER 37
CODE	EWD75X75	EWD70X40	EWD60X42	EWD50X50	EWD37X37
SUITABLE FOR	Railing posts, louver & screen structures, facade features, interior and exterior baffle walls & ceilings.	Railing hand rails, railing verticals, louvers, screens, ducting coverings, facade features, interior and exterior baffle walls & ceilings.	Railing hand rails, railing verticals, louvers, screens, ducting coverings, facade features, interior and exterior baffle walls & ceilings.	Railing hand rails, railing verticals, louvers, screens, ducting coverings, facade features, interior and exterior baffle walls & ceilings.	Railing hand rails, railing verticals, louvers, screens, ducting coverings, facade features, interior and exterior baffle walls & ceilings.
MANUFACTURING TECHNOLOGY	STANDARD WPC	STANDARD WPC	STANDARD WPC	STANDARD WPC	STANDARD WPC
SURFACE FINISH	BRUSHED	BRUSHED	BRUSHED	BRUSHED	BRUSHED
COLOUR TONE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
THICKNESS	75 MM	40 MM	42 MM	50 MM	37 MM
WIDTH	75 MM	70 MM	60 MM	50 MM	37 MM
LENGTH MM/FT	2.90 / 9'6"	2.90 / 9'6"	2.90 / 9'6"	2.90 / 9'6"	2.90 / 9'6"

ADVANTAGES

- 

Architectural Flexibility
- 

UV & Weather Resistant
- 

Low Maintenance
- 

Visual Cohesion
- 

Natural Wood Appeal

CERTIFICATIONS



CONTACT US